

## Softlight Tilt Downlight V2




Softlight Tilt with glare control 'snoot'



Softlight Tilt without glare control





## FACT FILE:



	<b><u>10W</u></b>	<b><u>20W</u></b>
<b><u>General Information</u></b>		
<b>Body Construction</b>	Polycarbonate / Aluminium Heat sink	Polycarbonate / Aluminium Heat sink
<b>Lens Type</b>	Acrylic cover	Acrylic cover
<b>Reflector, 38° spread.</b>	Metalized polycarbonate with faceted, non tarnish finish.	Metalized polycarbonate with faceted, non tarnish finish.
<b>Compliance</b>	SANS 60598	SANS60598
<b>IP Rating</b>	IP 20	IP 20
<b>Control Type</b>	Standard - no control, on or off 1-10V control available DMX control available DALI control available	Standard - no control, on or off 1-10V control available DMX control available DALI control available
<b><u>Electrical Information</u></b>		
<b>Electrical Class</b>	Class 2	Class 2
<b>Socket Options</b>	Supplied with cabtyre and plugtop	Supplied with cabtyre and plugtop
<b>Supply Voltage</b>	230V AC	230V AC
<b>Surge Protection</b>	1kV in Power Supply Unit	1kV in Power Supply Unit
<b>Power Factor</b>	Better than 0,95	Better than 0,95
<b><u>Optical Information</u></b>		
<b>CRI</b>	Better than 80	Better than 80
<b>CCT</b>	3000K warm white 4000K Neutral White 5000K Soft white	3000K warm white 4000K Neutral White 5000K soft white
<b><u>Performance</u></b>		
<b>Total Circuit load and Lumens</b>	1300 lumens 10W (at source)	2600 lumens 20W (at source)
<b><u>Operating Conditions</u></b>		
<b>Operating Temperature range</b>	-20°C to + 40°C	-20°C to + 40°C
<b>Weight</b>	250g	300g

