






Full spectrum 'Sun Like' white LEDs

Far Red LEDs on a separate circuit

Back View



savings (when compared

providing better quality

to HID) as well as

light than HID.







FACT FILE:

General Information	TACTILL.
Body Construction	Extruded marine grade aluminium, Aluminium end caps.
Lens Type	UL V5 (flame proof) UV stable Macrolon
Recommended Height Installation	From 3m and higher
Compliance (On PSU)	☐ EN 55015// EN 6100-3-2// EN61347-2-13// EN 61547// EN 62384// ☐ EN 60598
IP Rating	☐ IP 55 ☐ Splash proof for wet environments
Control Type	0 - 10V dimmable and on/off as standard. DALI or DMX or KNX on request
Electrical Information	
Electrical Class	Class 2
Socket Options	IP rated tools free from LED housing to power supply unit.
Supply Voltage	90 - 305 V AC 50/60Hz
Surge Protection	Between L and N = 6kV Between L and E = 10kV
Power Factor	Better than 0.98
Optical Information	
ССТ	4000K standard – 5000K or 6000K and higher on request.
CRI	Better than 84 as standard – up to +95 on request
<u>Performance</u>	
Total Circuit load and Lumens	650W total circuit load with far red activated – 105 900 Lumens (1890 μMol) 600W – 'Sun Like white' only 50W – 'Far Red' only
Operating Conditions	
Operating Temperature range	From minus 20°C to 45°C ambient temperature.
Cooling	Passive
Weight	Main LED body – 4kg. Power supply 7 kg total 11kg.

Guarantee/Warranty – 5 years – subject to our terms and conditions







FACT FILE:

